

Adding Freshness into your recipes!



 **THE MIDDLEBY CORPORATION**

Middleby Celfrost brings to India, a truly world class range of Gastronorm refrigeration products, that enhance the skills of modern kitchen professionals. With Celfrost Professional, you say good-bye to power-guzzling, rust-catching and crudely fabricated refrigeration systems and actually enjoy the benefits of sturdy equipment built with Stainless Steel; flawless European controls; reliable European refrigeration system, energy saving design and dependable after sales service support.

Refrigerated Reach in Cabinets

Celfrost Professional Reach In Cabinets suitable for 2 x GN 1/1 sizes are built in SS304 with reliable Danfoss / Embraco or equivalent compressors, LED temperature display, rounded internal edges for complete hygiene, removable magnetic gaskets for ease of cleaning, self closing doors with heaters to prevent condensation and heavy duty lockable castors. Available in Chillers or Deep Freezers with two or four door options; a choice of Static or Ventilated refrigeration; and in 600 & 1200 ltr. capacities.

Features:

- Rounded internal edges
- Removable magnetic gaskets
- Self closing doors
- Auto defrost
- Eco friendly refrigerant
- Food grade steel
- Uniform cooling
- Adjustable trays



GN 650 TNM (New)/
GN 650 BTM (New)
GN 600 TNM / GN 600 BTM*



GN 1410 TNM (New)/
GN 1410 BTM (New)
GN 1200 TNM*



GN 2100 TN
GN 2100 BT

GN 3100 TN
GN 3100 BT

Undercounters

While retaining the basic features of the Reach in Cabinets mentioned above, these refrigerated work tables, mounted on heavy duty lockable castors, pull out condensing unit, combine storage and preparation thereby enhancing the effectiveness of kitchen professionals and are suitable for GN 1/1 sizes. Chillers or Deep Freezers available in 2 and 3 door options.

Prep Counters

Celfrost Professional Prep Counters desserts and more. Mounted on castors and available in 2 and 3 doors, frost free & static with fan assist cooling variants.



SH 2000/800
SH 2100/800*



PSS 200*
PSE 201*
(Also available in 3 doors
model PSS 300* & PSE 301*)



SH 3000/800
SH 3100/800*

*Static Cooling & Manual Defrost.

*SH 2100/800 & SH 3100/800 are in SS 201

Saladettes & Countertop Displays

The Saladettes come with a refrigerated GN compatible top (Pans not included) that can take in frozen yogurt toppings, salads etc. It also has a night cover. 2/3 Door Refrigerated section underneath is handy to store additional foodstuff. The Countertop display comes with a glass sneeze guard; is equipped with its own refrigeration unit and accepts GN ¼ pans (not included).




S 900/SE 900

SE 903



VRX 1200/330, VRX 1400/330



Blast Chillers & Shock Freezers

The powerful Celfrost Professional Blast Chillers / Freezers are most ideal for reducing the temperature of cooked food from 80°C to 3°C or -18°C rapidly, thereby rendering it safe from bacterial growth and fit for ensuing storage and consumption later on. Available in 4 capacities, they are suitable for both GN 1/1 and 400x 600 mm tray sizes.



D3/D5

D10/D14

Gastronorm (GN) Dimensions : L x W

GN 1/1	>	530 mm x 327 mm
GN 1/2	>	327 mm x 265 mm
GN 1/3	>	327 mm x 176 mm
GN 2/3	>	354 mm x 325 mm
GN 1/4	>	265 mm x 163 mm
GN 1/6	>	176 mm x 163 mm

Depth in case of pans can vary from 65, 100 or 150 mm
*GN Pan/Tray is not part of unit.

Frost Top & Cooling Well



3F

GN 3V

E-Series - Ventilated Reach Ins & Undercounters

Bigger space inside due to Insulated Evaporator at top in Reachins with all essential features like Removable gaskets, heavy duty castors, GN compatible, Danfoss / Embraco Compressor, Slide out Condenser unit (in undercounters), Digital controller, lock and many more to make it user friendly and hassle-free operation.



GN 2200 TNE/GN 2200 BTE
(Also available in 3 door models GN 3200 TNE/GN 3200 BTE)



GN 700 TNME / GN 700 BTME



GN 1500 TNME / GN 1500 BTME

Technical Specifications

Product	Model	Dimension (WxDxH) mm	Volume (in ltrs.)	Design (GN Compatibility)	No. of Doors	No. of shelves	Temperature Range (0C)	Input Power (in watts)	Refrigerant
Reach-in Refrigerators (Ventilated Cooling)	GN 650 TNM (New)	680 x 800 x 2010	600	2 x GN 1/1	2	3	2 to 8°C*	375	R134a
	GN 1410 TNM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	4	6	2 to 8°C*	800	R134a
	GN 700 TNME	740 x 830 x 2010	650	2 x GN 1/1	2	3	2 to 8°C*	400	R290
	GN 1500 TNME	1480 x 830 x 2010	1300	2 x GN 1/1	4	6	2 to 8°C*	670	R290
Reach-in Refrigerators (Static Cooling)	GN 600 TNM	680 x 810 x 2000	600	2 x GN 1/1	2	3	2 to 8°C*	375	R134a
	GN 1200 TNM	1340 x 810 x 2000	1200	2 x GN 1/1	4	6	2 to 8°C*	600	R134a
Reach-in Freezers (Ventilated Cooling)	GN 650 BTM (New)	680 x 800 x 2010	600	2 x GN 1/1	2	3	-18 to -22°C*	800	R404a
	GN 1410 BTM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	4	6	-18 to -22°C*	1060	R404a
	GN 700 BTME	740 x 830 x 2010	650	2 x GN 1/1	2	3	-18 to -22°C#	800	R290
	GN 1500 BTME	1480 x 830 x 2010	1300	2 x GN 1/1	4	6	-18 to -22°C#	1060	R290
Reach-in Freezer (Static Cooling)	GN 600 BTM	680 x 810 x 2000	600	2 x GN 1/1	2	3	-10 to -20°C*	800	R404a
Undercounter Chillers (Ventilated Cooling)	GN 2100 TN	1360 x 700 x 860	282	1 x GN 1/1	2	2	2 to 8°C*	375	R134a
	GN 3100 TN	1795 x 700 x 860	417	1 x GN 1/1	3	3	2 to 8°C*	375	R134a
	GN 2200 TNE	1360 x 700 x 850	282	1 x GN 1/1	2	2	2 to 8°C*	375	R600a
	GN 3200 TNE	1795 x 700 x 850	417	1 x GN 1/1	3	3	2 to 8°C*	375	R600a
Undercounter Freezers (Ventilated Cooling)	GN 2100 BTM	1360 x 700 x 860	282	1 x GN 1/1	2	2	-10 to -20°C*	800	R404a
	GN 3100 BTM	1795 x 700 x 860	417	1 x GN 1/1	3	3	-10 to -20°C*	880	R404a
	GN 2200 BTE	1360 x 700 x 850	282	1 x GN 1/1	2	2	-10 to -20°C#	875	R600a
	GN 3200 BTE	1795 x 700 x 850	417	1 x GN 1/1	3	3	-10 to -20°C#	890	R600a
Prep Counters (Ventilated Cooling)	SH 2000/800	1510 x 800 x 1050	337	6 x GN 1/3	2	2	2 to 8°C**	335	R134a
	SH 2100/800	1510 x 800 x 1085	337	6 x GN 1/3	2	2	2 to 8°C**	375	R290
	SH 3000/800	2020 x 800 x 1050	497	10 x GN 1/4	3	3	2 to 8°C**	495	R134a
	SH 3100/800	2020 x 800 x 1050	497	10 x GN 1/4	3	3	2 to 8°C**	400	R290
Prep Counters (Static Cooling with Fan Assist)	PSS 200	900 x 700 x 1010	240	5 x GN 1/6	2	2	2 to 8°C**	335	R134a
	PSS 201	900 x 700 x 970	240	8 x GN 1/6	3	3	2 to 8°C**	350	R290
	PSS 300	1368 x 700 x 1010	360	5 x GN 1/6	2	2	2 to 8°C**	495	R134a
	PSS 301	1365 x 700 x 970	360	8 x GN 1/6	3	3	2 to 8°C**	375	R290
Counter Top Displays (Static Cooling)	VRX 1200/330	1200 x 335 x 225**	-	5 x GN 1/4	-	-	2 to 8°C**	209	R134a
	VRX 1400/330	1400 x 335 x 435**	-	6 x GN 1/4	-	-	2 to 8°C**	209	R134a
Saladette	S 900	900 x 700 x 850	-	2 x GN 1/1	2	2	2 to 8°C**	245	R134a
	SE 900	900 x 700 x 850	-	+ 2 x GN 1/4	2	2	2 to 8°C**	350	R290
	SE 903	1365 x 700 x 970	-	4 x GN 1/1	3	3	2 to 8°C**	375	R290
Frost Top	3F	1119 x 695 x 432	NA	NA	NA	NA	-10°C	500	R134a
Ventilated Cooling Well	GN 3V (GN-3L)	1122 x 688 x 636	NA	3 x GN 1/1	NA	NA	2 to 8°C	280	R134a

Product	Model	Exterior Dimension (WxDxH) mm	Internal Dimension (WxDxH) mm	Pan Support (GN 1/1)	Pan Support (400 x 600 mm)	Net Weight (in kgs)	Power Supply	Refrigerant	Temperature Drop (°C)	Input Power (in watts)	Mode of Refrigeration
Blast Chillers/Freezers	D3	800 x 815 x 945	660 x 640 x 330	3 Sets	3 Sets	80	230V/50Hz	R404a	90°C to 3°C in 90 minutes	703	Ventilated
	D5	800 x 815 x 1015	660 x 640 x 400	5 Sets	5 Sets	95	230V/50Hz	R404a		801	Ventilated
	D10	800 x 815 x 1645	660 x 640 x 870	10 Sets	10 Sets	150	230V/50Hz	R404a	90°C to -18°C in 240 minutes	1298	Ventilated
	D14	800 x 815 x 2117	660 x 640 x 1170	14 Sets	14 Sets	210	380V/50Hz/3Ph	R404a		2000	Ventilated

* Tested to perform under ambient temperature of 42°C

** Tested to perform under ambient temperature of 32°C

Tested to perform under ambient temperature of 38°C

With a view to ensure ongoing product enhancement/development, Middleby Celfrost reserves the right to change any specification, without prior notice.

ISO9001:2000 CE CCC UL RoHS

Note: 1. Images are for representation, actual product might vary. 2. Specifications might change due to continuous product development. 3. Accessories are optional.



Middleby Celfrost Innovations (P) Ltd.

Corp. Office : Unit Nos. SF-713 — 716, 7th Floor, JMD Megapolis, Sohna Road, Sector 48, Gurgaon - 122 018, Haryana, India.

Tel. : +91 124 482 8500, Fax : +91 124 427 9663, E-mail : corp@middlebycelfrost.com, Web : www.middlebycelfrost.com

Toll Free Customer Service No.: **1800-102-1980** • **service.india@middlebycelfrost.com**

ONE PARTNER. ONE TEAM. MANY SOLUTIONS.



For sales related queries :-

Call: +91 124 4828500 • Email: sales@middlebycelfrost.com